	Cage Code:	Title:	Date:	Rev:	Model no:
HILL ADDRESS DUCTOR	02WLO	PRODUCT DATA	12/14/09	None	HL1-130
		(subject to change)			

This document describes the performance of a high power limiter. Limiters are not reciprocal devices. Please be sure that high power is applied at the input port only.

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
1	POWER SPECIFICATION	IN BAND				-
1.1	FREQUENCY		100	3000	MHz	
1.2	PEAK POWER			100	WATTS	
1.3	PULSE WIDTH			CW	μs	
1.4	DUTY			CW	%	
1.5	AVERAGE POWER			100	WATTS	
1.6	CW POWER			100	WATTS	
2	POWER SPECIFICATIONS	GUARD BAND				
2.1	FREQUENCY		3000	3500	MHz	
2.2	PEAK POWER			10	WATTS	
2.3	PULSE WIDTH			1	μs	
2.4	DUTY			1	%	
2.5	AVG. POWER			1	WATTS	
3	POWER SPECIFICATIONS	OUT OF BAND				
3.1	FREQUENCY			>3500	MHz	
3.2	PEAK POWER			1	WATTS	
3.3	PULSE WIDTH			1	μs	
3.4	DUTY			1	%	
3.5	AVG. POWER			0.01	WATTS	
4	OPERATING FREQUENCY		100	3000	MHz	
5	INSERTION LOSS					
5.1	LOSS			0.9	dB	
6.1	FLAT LEAKAGE			+10	dBm	
7	SPIKE				dBm	NOT SPECIFIED
7.1	SPIKE ENERGY				erg	NOT SPECIFIED
8	RECOVERY TIME				μs	NOT SPECIFIED

	Cage Code:	Title:	Date:	Rev:	Model no:
	02WLO	PRODUCT DATA	12/14/09	None	HL1-130
run i nginaaring tacaten		(subject to change)			

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
9	VSWR					
9.1	SOURCE			1.5:1		
9.2	UNIT			1.5:1		
9.3	LOAD			1.5:1		
9.4	CHARACTERISTIC IMPEDANCE					50 Ohms
9.5	AC Coupling					This Unit has internally mounted DC block
10	CONNECTORS					
10.1	RF					SMA Female on Input & Output
12	MECHANICAL					
12.1	WEIGHT			4.6	Oz.	
12.2	OUTLINE					DWG 4407
13	ENVIRONMENTAL					
13.1	OPERATING TEMPERATURE		-20	+70	°C	
13.2	STORAGE TEMPERATURE		-55	+85	°C	
13.3	VIBRATION LEVEL					Ground Mobile
14	SCREENING					SCREEN PER QP-121 LEVEL 3

