

	Cage Code:	Title:	Date:	Rev:	Model no:
	02WLO	PRODUCT DATA (subject to change)	08/10/2009	None	HL3-082

This document describes the performance of a high power limiter. This limiter is passive i.e.; no externally applied bias voltage or control signal is required.

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
1	POWER SPECIFICATION	IN BAND				
1.1	FREQUENCY		6.8	9.6	GHz	
1.2	PEAK POWER			10	WATTS	
1.3	PULSE WIDTH			1	μS	
1.4	DUTY			1	%	
1.5	CW POWER			10	WATTS	
2	POWER SPECIFICATIONS	GUARD BAND				
2.1	FREQUENCY		9.6	10.5	GHz	
2.2	PEAK POWER			10	WATTS	
2.3	PULSE WIDTH			1	μS	
2.4	DUTY			1	%	
2.5	CW POWER			1	WATTS	
3	POWER SPECIFICATIONS	OUT OF BAND				
3.1	FREQUENCY			>10.5	GHz	
3.2	PEAK POWER			1	WATTS	
3.3	PULSE WIDTH			1	μS	
3.4	DUTY			1	%	
3.5	CW POWER			0.1	WATTS	
4	OPERATING FREQUENCY		6.9	7.1	GHz	
5	INSERTION LOSS					
5.1				1.2	dB	
6	FLAT LEAKAGE					
6.1				15	dBm	
7	SPIKE					
7.1				0.1	erg	
8	RECOVERY TIME					
8.1				0.5	μS	

Federal Cage Code 02WLO



Cage Code: 02WLO

Title: **PRODUCT DATA**
(subject to change)

Date: 08/10/2009

Rev: None

Model no: **HL3-082**

ITEM NO	CHARACTERISTIC	CONDITIONS	MIN	MAX	UNITS	COMMENTS
8	VSWR					
81				1.6:1		
9	CONNECTORS					
9.1	RF INPUT					SMAF
9.2	RF OUTPUT					SMAM
10	MECHANICAL					
10.1	WEIGHT			2	Oz.	
10.2	OUTLINE					SEE DWG 2695 below
11	ENVIRONMENTAL					
11.1	OPERATING TEMPERATURE		-40	+85	°C	
11.2	STORAGE TEMPERATURE		-55	+85	°C	
11.3	VIBRATION LEVEL					GROUND MOBILE
11.4	PRESSURIZATION			N/A	PSIG	
12	SCREENING					SCREEN PER QP-121 LEVEL 3

PRODUCT DATA
(subject to change)

Date:
08/10/2009

Rev:
None

Model no:
HL3-082

